

Pathfinder Ultra Series



The Ultimate scan, print and apply solution.

RF and Batch versions available

From Concept to Checkout

PAXAR

We Make Your Sales Work(s)[™]



“Concept to Checkout” By Owen Smith

Pathfinder Ultra – Simply the best one piece printer

Unrivalled by anything else in the market, the Pathfinder Ultra series of printers is the world's best and only one-piece handheld solution.

It offers:

- Scanning.
- Data collection and processing.
- Label print and application.

It combines leading edge technology with one of the world's smallest laser scanners to give an intelligent system that can print and apply labels in one stroke to increase accuracy and eliminate key entry errors.

Its rugged design means it can withstand the toughest of environments and coupled with the ergonomic design it is also comfortable and lightweight to hold. Using the Pathfinder Ultra can save not only time and money but can also help improve productivity by up to 89% eliminating manual tasks which can lead to mistakes being made.



Retailers

Price Management/Mark-downs – Operate anywhere in the store to create labels and tags.



Shelf edge labelling

Update shelf labels with correct pricing. Produce out of stock labels. Remotely request new shelf edge labels.



Logistics and Distribution

Picking and Packing– No need for a picking slip. The host directs the operator via the RF network to pick, label, apply and pack on the go.



Manufacturing

Inventory Control - Direct goods coming in to their correct unloading bay/location and update stock system in real time.

Key features of the Ultra Series:

- ✓ Easy drop-in supply loading.
- ✓ Portable and lightweight.
- ✓ Fast imaging with a 32-bit processor.
- ✓ RF and Batch versions available.
- ✓ 2.4 GHz/802.11b WIFI compatible.
- ✓ Lithium Ion battery for improved performance.
- ✓ Wide range of accessories to include: on demand sensor, 4 station battery charger, holster and PC software.

6032 additional features:

- ✓ 15 characters, 4 lines plus status line.
- ✓ Print speed 51mm (2") per second.
- ✓ Keypad with 23 keys

6037 additional features:

- ✓ 16 characters, 4/8 lines plus status line.
- ✓ Print speed 102mm (4.0") per second.
- ✓ Keypad with 34 keys.

The world's smallest integrated label scanner



RF capability.

In addition the series also features an RF system which allows users to collect, process, print and apply information in real time using open architecture. The system operates on all 2.4 GHz/802.11b compliant WIFI compatible RF backbones, including for example Symbol and Cisco.

Product Specification

Standard Features

Printing Method

Thermal Direct

Dimensions

Height 165mm (6.50")

Width 197mm (7.75")

Depth 83mm (3.25")

Weight 0.95kg (2.09lbs)

Printhead

51mm wide (2")

203 DPI – 8 dots/mm

Keypad

6032 – 23 keys

6037 – 34 keys

Display

6032 - 4 lines, 15 characters plus status line, back lit LCD

6037 – 4/8 lines, 16 characters plus status line, backlit LCD

PC/Host Interface

RS 232 Serial

Memory

1MB RAM and 2MB Flash

Expandable Flash memory (6037)

PCMCIA compact Flash

Programming Languages

6032 – ADK (application development kit) available from Paxar

6037 – C/C++ (Full software development kit also available)

For further information please contact your local Paxar representative

Scanner

Laser high intensity scan engine

RF communications

802.11a and 802.11b compatible drivers

Internal antenna

PCMCIA RF card interface

Standard Fonts

Bitmapped, TrueType and International Fonts

Bar Code Symbologies

6032 & 6037

- EAN 8, 13, +2, +5
- UPC A, E, +2, +5
- Interleaved 2 of 5
- Extended Code 39
- CODABAR (NW7)
- Code 128
- Code 93
- MSI

6037 can also print

- MAXICODE
- PDF417
- POSTNET
- Datamatrix

Optional Accessories

- On demand sensor
- Single or 4 station battery charger
- AC Power supply
- MPCL/ADK Toolbox Utilities
- Hip/Hand strap
- PC software

Supply Sizes

Widths 51mm (2.0")

Lengths 102mm (4.0")

Maximum Print Area

51mm x 102mm (2.0" x 4.0")

Performance

Power

7.4V Lithium Ion Battery

300+ charge cycles

Printing Rate

6032 only

51mm (2.0") per second

6037 only

102mm (4.0") per second

Environment

Temperature

Operating

40°F to 110°F (4°C to 43°C)

Humidity

5% to 90% non condensing

Paxar UK Ltd.
Tel: +44 (0)1279 786000
Fax: +44 (0)1279 786100
www.paxar-europe.com
Contact enquiries@paxar.co.uk

From Concept to Checkout

PAXAR

We Make Your Sales Work(s)[™]



BRA015

©2002 Paxar UK Ltd

All rights reserved - Printed in the UK