

FUZZYSCAN A570

2D Handheld Imager



The deluxe and stylish 2D handheld imager

Powered by Cino's exclusive FuzzyScan imaging technology, the A570 is capable of reading most real-world challenging and problematic barcodes. Boasting a stylish yet ergonomic design, versatile functionality, and FuzzyScan DNA, the A570 help enhance your scanning experience with exceptional cost-performance value for retail, hospitality, and healthcare applications.

- Reads most challenging and problematic barcodes
- Superior first pass read rate
- Withstands 1.6m drops to concrete
- Clear audio and visual feedback
- Optional vibration function for tactile confirmations
- One-Step configuration through iCode
- Advanced data formatting and processing with DataWizard Premium
- Inherits the powerful FuzzyScan DNA

Scan All Your Needs

Powered by exclusive FuzzyScan Imaging technology, the A570 imager is capable of reading a vast array of challenging and problematic barcodes. The A570 imager is capable of scanning wrinkled, dirty, or soiled barcodes that are displayed on paper, plastic, metal, digital screens, and curved surfaces.

Cutting Edge Imaging Technology

Powered by state-of-the-art AI-based machine vision, the exclusive FuzzyScan imaging technology is a performance-driven innovation. Incorporated with an advanced optical design and a powerful hardware platform, all Cino Imagers deliver unrivaled scanning speed and accuracy across all types of real-world barcodes.

Economical Excellence

The A570 imager offers the perfect balance of performance and affordability, making it the most economical choice for commercial applications. Despite its affordable price point, it still delivers outstanding speed and point-and-shoot scanning simplicity, making it a great option for any business. The A570 imager does not compromise on performance and is suitable for most commercial applications.

Enhanced User Experiences

Designed with sharp aiming and multifaceted notification feedback via visual, audio, as well as tactile indications, the A570 delivers superior usability and a great user experience.



FUZZYSCAN DNA

Clear Audio and Visual Feedback

The A570 imager uses audio and visual indicators to indicate its various statuses. The Imager has a loud beeper with an adjustable volume and tone. The LED lights emit conspicuous and programmable multi-color signals to help users clearly identify the current status at a quick glance.

Tactile Feedback Option

Beeping sounds are considered disruptive in certain circumstances. Vibration is available as an option on this imager to provide tactile feedback to users. This is suitable for both quiet and noisy environments.

Stylish and Discreet

The A570 boasts a sleek and elegant design that seamlessly blends into any commercial setting. Its attractive appearance is matched by an ergonomic handle that offers a natural and comfortable grip. Not only does it look great, but its durable enclosure can withstand even the toughest of accidental drops, ensuring it maintains its stylish look for years to come.

Value beyond Measure

FuzzyScan DNA is a collection of unique features that come with all Cino Imagers at no additional costs. Aside from the exclusive FuzzyScan Imaging technology, Cino Imagers also provide the following features to deliver exceptional value beyond barcode scanning:

- **DataWizard Premium**, a unique feature to perform advanced data formatting and complex data processing to fit specific needs without modifying host programs such as drivers license parsing.
- **iCode**, a macro command barcode that allows one-step configuration with a single scan.
- **Multilingual Edge**, a useful feature that enables data output in your desired language. Aside from Western European and Latin languages, it also supports many Asian languages such as Simplified Chinese, Traditional Chinese, Korean, Japanese, Thai, Hindi, and so on.
- **Smart Scene**, a choice of several preset configurations for various application scenarios to achieve optimal scanning performance.
- **Security Plus**, a user-defined security mechanism that prevents the access of unauthorized barcode Imagers.
- **FuzzyScan Enabling Solution**, a suite of software utilities, including PowerTool, ConnectWizard, and SDK, for the easy configuration, management, and deployment of Imagers.

SPECIFICATIONS

Performance Characteristics

Image Sensor	1120 x 768 Pixels
Print Contrast	18% minimum reflectance difference
Light Source	Warm white LED
Imager Field of View	36.5 ° H x 24.9 ° V
Minimum Resolution	3.0 mil Code 39 5.0 mil DM
Reading Range *1	13 mil (0.33mm) UPC/EAN up to 17.1"
Roll, Pitch, Skew	Roll: 360 °; Pitch: ± 70 °; Skew: ± 50 °
Configuration Setup	FuzzyScan Barcode commands FuzzyScan iCode FuzzyScan PowerTool
Data Processing	DataWizard Premium
Host Interfaces	USB HID (USB Keyboard) USB VCOM (USB COM port emulation) USB OEM POS Standard RS232
User Interfaces	Blue LED for power, good read and status indications Programmable beeper Optional vibrate function

Electrical Characteristics

Operating Voltage	5VDC ± 10%
Operating Current	Operating : Typical 285mA @ 5VDC Standby : Typical 185mA @ 5VDC

Physical Characteristics

Dimensions	165.0 mm (L) x 64.7 mm (W) x 38.7 mm (D) 6.50 in. (L) x 2.55 in. (W) x 1.52 in. (D)
Weight	106g (cable excluded)
Color	Classic Black, Ivory White

1. The Reading Range are measured under Cino's test environmental condition.
2. Codablock F, Code 16K, Code 49, and Chinese Sensible (Han Xin) Code are available upon request.

Supported Symbolologies

1D Linear Codes	Code 39, Code 39 Full ASCII, Code 32, Code 128, GS1-128, Codabar, Code 11, Code 93, GS1 DataBar, Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5, IATA, UPC/EAN/JAN, UPC/EAN/JAN with Addendum, Telepen, MSI/Plessey & UK/Plessey
2D Codes *2	PDF417, Micro PDF417, Composite Codes, DataMatrix, MaxiCode, QR Code, MicroQR, Aztec, Codablock F, Code 16K, Code 49, Chinese Sensible (Han Xin) Code
Postal Codes	Australian Post, US Planet, US POSTNET, Japan Post, Posi LAPA 4 State Code, German Post, British Post, Intelligent Mail, Korean Post, Dutch KIX Post, China Post

User Environment

Drop Specification	Withstand multiple 1.6m/5.2ft. drops to concrete
Environmental Sealing	IP 41
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Humidity	0% to 95% relative humidity, non-condensing
Ambient Light Immunity	0 ~ 100,000 lux
ESD Protection	Functional after 15KV discharge

Safety & Regulatory

EMC	CE, UKCA, FCC, BSMI, RCM, KC, VCCI
Safety	LED Eye Safety IEC62471, Exempt Group
Environmental	Compliant with RoHS and REACH

Accessories

Cables	RS232 Serial Cable USB-A Cable USB-C Cable USB Power Cable
Others	US100 SmartStand Universal Holder Power Supply Unit (5VDC, 2A outlet)